
# **SWSL1412HD**Electric Hydraulic-drive Scissor-type Aerial Work Platform


## **SUNW**ÁRD


Dimension					
Work	ing height*	14m			
Α	Platform height maximum	12m			
В	Platform height (stowed)	1.49m			
С	Platform length	2.27m			
	Slide-out platform extension deck	0.9m			
D	Platform width	1.15m			
Е	Stowed height (rails up)	2.63m			
	Stowed height (rails down)	2.09m			
F	Overall length	2.47m			
G	Overall width	1.17m			
Н	Wheelbase	1.87m			
I	Ground clearance (stowed)	0.11m			
J	Ground clearance (raised)	0.02m			

Performance	
Lift capacity	320kg
Lift capacity (extension deck)	113kg
Max. Occupants	2
Drive speed (stowed)	3.2km/h
Drive speed (elevated)	0.8km/h
Turning radius (inside)	0m
Turning radius (outside)	2.2m
Raise / lower speed	62s / 42s
Gradeability**	25%
Max. allowable working angle (lateral / longitudinal)	1.5° / 3°
Controls	Proportional
Wheel driver	Dual front wheel
Multiple disc brakes	Dual rear wheel
Tires	381mm×129mm
Battery	4×12V/300Ah
Charger	24V/30A
Weight	2980kg



<sup>\*</sup> Climbing ability is suitable for driving on slopes; Refer to Operator Manual for slope level.







### **SWSL1412HD**

#### Electric Hydraulic-drive Scissor-type Aerial Work Platform











#### Standard features

◆ Proportional control	Extended platform	◆ Folding guardrails platform	◆ Self-lock gate on platform
◆ Solid tire	◆ Hour meter	Standard transport forklift hole	Safety maintenance support rod
◆ Horn	Flashing beacon	Action beep	◆ Dual front wheel drive
◆ Pit protection device	Emergency descent system	◆ Emergency stop button	◆ Automatic brakes system
Tilt sensor with alarm	◆ Charging protection system	◆ Fault diagnosis system	◆ Overload protection system

#### Options features

◆ Air line to platform	AC power to platform	GPS tracking system	◆ Platform work lights
◆ Maintenance-free battery	Lithium battery and management system	Intelligent interconnection system	

